



GALGO^{MR}

PRE-Q[®]



SA

[Spread Axle]



REGIONAL



| código | inch | mm | /32 | mm |
|----------|-------|-----|-----|------|
| 75 SA 18 | 7 5/8 | 194 | 18 | 14.3 |
| 80 SA 18 | 8 | 203 | 18 | 14.3 |
| 82 SA 18 | 8 2/8 | 210 | 18 | 14.3 |
| 85 SA 18 | 8 5/8 | 219 | 18 | 14.3 |
| 90 SA 18 | 9 | 229 | 18 | 14.3 |
| 92 SA 18 | 9 2/8 | 235 | 18 | 14.3 |
| 94 SA 18 | 9 4/8 | 240 | 18 | 14.3 |
| 97 SA 18 | 9 7/8 | 251 | 18 | 14.3 |

| | |
|--------------------|--|
| Tracción: | Media |
| Velocidad: | Moderada |
| Hombro redondeado: | Sí |
| Ala: | No |
| Sentido de giro: | No |
| Tipo de camino: | Carreteras secundarias sinuosas y con pendientes. |
| Beneficios: | Ayuda a la auto limpieza. |
| Cualidades: | Diseño de 4 costillas con elementos transversales en las costillas exteriores para mayor tracción y expulsión de piedras. Hombro redondeado. Costillas centrales escalonadas y con ángulos variables para autolimpieza y agarre. |

Recomendado:

Eje:

Tipo de llanta:



www.galgo.com.mx

Medidas de llantas recomendadas

| | | |
|----------|-------------|-------------|
| 9.00R20 | 215/75R17.5 | 255/70R22.5 |
| 10.00R20 | 225/70R19.5 | 255/80R22.5 |
| 10R22.5 | 225/75R16 | 275/70R22.5 |
| 11.00R20 | 235/75R17.5 | 275/80R22.5 |
| 11R22.5 | 235/85R16 | 275/80R24.5 |
| 11R24.5 | 245/70R19.5 | 295/75R22.5 |
| 12R22.5 | 245/75R16 | |
| 12R24.5 | 245/75R17.5 | |